

LANDI

# C20 Pro C20 Pro SE

## ECR Terminal



**Elevate user experience to  
new heights with futuristic terminal.**

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.



## | SPECIFICATIONS

<b>Processor</b>	Qualcomm Octa-core, up to 2.4GHz	<b>Size</b>	23.5cm x 36cm x 36cm 9.25" x 14.17" x 14.17"
<b>OS</b>	Android 13 GMS	<b>Connectivity</b>	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4G and 5G ETH: 1000M Bluetooth 5.0, support BLE Optional, 4G fallback 3G and GPRS (Only for C20 Pro 4G)
<b>Memory</b>	Internal: 4GB RAM+64GB FLASH 8GB RAM+128GB FLASH (Optional) External: Micro SD Card (Up to 2TB)	<b>Positionning</b> (Only For C20 Pro 4G)	Optional, GPS, GLONASS, BEIDOU
<b>Main display</b>	15.6", 1920x1080, FHD capacitive multi-touch	<b>Audio</b>	Speaker: 5W, 100dB@1m, Dual Speaker Headset: 3.5mm audio jack MIC: Dual Microphone
<b>Customer display</b>	Optional 1:None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3: 10.1"Premium CFD (1280x800,Touch panel, QR Camera, NFC)	<b>Camera</b> (Optional)	Optional 1: None Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1" Premium CFD) Optional 3: Facial recognition ability camera (USB device, plug into Main display edge expansion port)
<b>Printer</b> (Only For C20 Pro)	80mm Thermal Printer, Diameter:80mm Print speed:200mm/s, Auto Cutter	<b>NFC</b>	Android NFC, ISO / IEC 14443, ISO15693 compliant, support Type A / B, Mifare, Felica (Only supported on the 10.1" Premium CFD)
<b>Ports</b>	1 USB Type-C, debug port, 4 USB Type-A 2.0+1 USB Type-A 3.0 1 RJ22 Serial port, 1 RJ45 Ethernet port, 1 RJ11 Cash drawer port 1 3.5mm Audio port, 1 MicroSD slot 1 Power port	<b>SAM/SIM slots</b> (Only For C20 Pro 4G)	1 SIM (Optional)
<b>Buttons</b>	1 Power key with indicator light (Red&blue) 2 Volume keys 1 Function key	<b>PSU</b>	19~20V/3.25A
		<b>Environment</b>	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Operating humidity: 10% to 90% non-condensing
		<b>Certification</b>	CE/CB/FCC/IC/RoHS/WEEE

